SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Lakier PVB 16

Creation date	10th June 2022		
Revision date	17th January 2025	Version	7.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier — Lakier PVB 16

Substance / mixture — mixture

UFI — WC00-Y0QU-6002-F0KJ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

Varnish for protecting PCBs

Main intended use

PC-PNT-1 — Aerosol paints and coatings

Mixture uses advised against

The product should not be used in ways other then those referred in Section 1.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Name or trade name	AG TermoPasty Grzegorz Gąsowski
Address	Kolejowa 33 E, Sokoły, 18-218 Poland
Identification number (CRN)	200133730
VAT Reg No	PL9661767714
Phone	+48 86 274 13 42
E-mail	msds@termopasty.pl
Web address	www.termopasty.com

Competent person responsible for the safety data sheet

Name	AG TermoPasty Grzegorz Gąsowski
E-mail	msds@termopasty.pl

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification of the mixture in accordance with Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Aerosol 1, H222, H229
Eye Dam. 1, H318
STOT SE 3, H336

Most serious adverse physico-chemical effects


Extremely flammable aerosol. Pressurised container: May burst if heated.

Most serious adverse effects on human health and the environment

Causes serious eye damage. May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

acetone
butan-1-ol

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H318	Causes serious eye damage.

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com

H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER.
P410+P412	Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances and additives specified below.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 Registration number: 01-2119471330-49-XXXX	acetone	20-40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	1
Index: 601-004-00-0 CAS: 106-97-8 EC: 203-448-7	butane	24-32	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	1
Index: 601-003-00-5 CAS: 74-98-6 EC: 200-827-9	propane	8-16	Flam. Gas 1, H220 Press. Gas (compressed gas), H280	
Index: 603-004-00-6 CAS: 71-36-3 EC: 200-751-6 Registration number: 01-2119484630-38-XXXX	butan-1-ol	5-10	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336	1
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25-XXXX	isopropanol	5-10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	1

Notes

1 *A substance for which exposure limits are set.*

Full text of all classifications and hazard statements is given in the section 16.

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com

SECTION 4: First aid measures

4.1. Description of first aid measures

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

Unlikely.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Inhaling vapours can cause corrosion of the breathing system. May cause drowsiness or dizziness.

If on skin

Not expected.

If in eyes

Causes serious eye damage.

If swallowed

Corrosion of the digestion system can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Use a self-contained breathing apparatus and full-body protective clothing. Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Extremely flammable aerosol. Pressurised container: May burst if heated. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale gases and vapours. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Ventilate the room. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water.

6.4. Reference to other sections

See the Section 7, 8 and 13.

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale gases and vapours. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Protect from sunlight. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

Content	Packaging type	Material of package
400 ml	airspray	FE
100 ml	airspray	FE

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union — **Commission Directive 2000/39/EC**

Substance name (component)	Type	Value
acetone (CAS: 67−64−1)	OEL 8 hours	1210 mg/m³
	OEL 8 hours	500 ppm

United Kingdom — **EH40/2005 Workplace exposure limits (Fourth Edition 2020)**

Substance name (component)	Type	Value
acetone (CAS: 67−64−1)	WEL 8h	1210 mg/m³
	WEL 8h	500 ppm
	WEL 15min	3620 mg/m³
	WEL 15min	1500 ppm
butane (CAS: 106−97−8)	WEL 8h	1450 mg/m³
	WEL 8h	600 ppm
	WEL 15min	1810 mg/m³
	WEL 15min	750 ppm
isopropanol (CAS: 67−63−0)	WEL 8h	999 mg/m³
	WEL 8h	400 ppm
	WEL 15min	1250 mg/m³
	WEL 15min	500 ppm

United Kingdom — **EH40/2005 Workplace exposure limits (Fourth Edition 2020)**

Substance name (component)	Type	Value
butan−1−ol (CAS: 71−36−3)	WEL 15min	154 mg/m³
	WEL 15min	50 ppm

Notes
Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com

DNEL

acetone			
Workers / consumers	Route of exposure	Value	Effect
Workers	Inhalation	2420 mg/m³	Acute effects local
Workers	Dermal	186 mg/kg bw/day	Chronic effects systemic
Workers	Inhalation	1210 mg/m³	Chronic effects systemic
Consumers	Dermal	62 mg/kg bw/day	Chronic effects systemic
Consumers	Inhalation	200 mg/m³	Chronic effects systemic
Consumers	Oral	62 mg/kg bw/day	Chronic effects systemic

butan-1-ol			
Workers / consumers	Route of exposure	Value	Effect
Workers	Inhalation	10 mg/m³	Chronic effects systemic
Consumers	Inhalation	55 mg/m³	Chronic effects systemic
Consumers	Oral	3.125 mg/kg	Chronic effects systemic

isopropanol			
Workers / consumers	Route of exposure	Value	Effect
Workers	Inhalation	500 mg/m³	Chronic effects systemic
Workers	Dermal	888 mg/kg bw/day	Chronic effects systemic
Consumers	Inhalation	89 mg/m³	Chronic effects systemic
Consumers	Dermal	319 mg/kg bw/day	Chronic effects systemic
Consumers	Oral	26 mg/kg bw/day	Chronic effects systemic

PNEC

acetone	
Route of exposure	Value
Drinking water	10.6 mg/l
Marine water	1.06 mg/l
Sea sediments	30.4 mg/kg of dry substance of sediment
Freshwater sediment	30.4 mg/kg of dry substance of sediment
Soil (agricultural)	29.5 mg/kg of dry substance of soil
Microorganisms in sewage treatment	100 mg/l

butan-1-ol	
Route of exposure	Value
Drinking water	0.082 mg/l
Marine water	0.0082 mg/l
Water (intermittent release)	2.25 mg/l
Freshwater sediment	0.178 mg/kg
Sea sediments	0.0178 mg/kg
Soil (agricultural)	0.015 mg/kg of dry substance of soil

isopropanol	
Route of exposure	Value
Drinking water	140.9 mg/l
Marine water	140.9 mg/l
Freshwater sediment	552 mg/kg of dry substance

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com

isopropanol	
Route of exposure	Value
Freshwater environment	552 mg/kg of dry substance
Soil (agricultural)	28 mg/kg of dry substance

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	gas
Colour	colourless
Odour	data not available
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
Flammability	data not available
Lower and upper explosion limit	data not available
Flash point	data not available
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	gas
Kinematic viscosity	data not available
Viscosity	44 mPa*s
Solubility in water	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	
Density	0.792 g/cm³
Relative vapour density	data not available
Particle characteristics	data not available
Form	liquid

9.2. Other information

Ignition temperature	380 °C

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

acetone					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD_{50}	5800 mg/kg		Rat (Rattus norvegicus)	
Inhalation (vapor)	LC_{50}	76000 mg/m³	4 hours	Rat (Rattus norvegicus)	
Dermal	LD_{50}	7400 mg/kg		Rabbit	
Dermal	LD_{50}	7400 mg/kg		Guinea-pig (Cavia aperea f. porcellus)	

butan-1-ol					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD_{50}	2292 mg/kg		Rat (Rattus norvegicus)	
Dermal	LD_{50}	3430 mg/kg		Rabbit	
Inhalation	LC_{50}	17.76 mg/l	4 hours	Rat (Rattus norvegicus)	

isopropanol					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Inhalation	LC_{50}	>5 mg/l	4 hours	Rat	
Oral	LD_{50}	>2000 mg/kg		Rat	
Skin	LD_{50}	>2000 mg/kg		Rabbit	

Skin corrosion/irritation

Based on available data the classification criteria are not met.

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com

Serious eye damage/irritation
Causes serious eye damage.

acetone				
Route of exposure	Result	Method	Exposure time	Species
Eye		OECD 405		

Respiratory or skin sensitisation
Based on available data the classification criteria are not met.

Germ cell mutagenicity
Based on available data the classification criteria are not met.

Carcinogenicity
Based on available data the classification criteria are not met.

Reproductive toxicity
Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure
May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure
Based on available data the classification criteria are not met.

Aspiration hazard
Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. Based on available data the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties
Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information
not available

SECTION 12: Ecological information

12.1. Toxicity
not available

Acute toxicity

acetone				
Parameter	Value	Exposure time	Species	Environment
LC_{50}	8800 mg/l	48 hours	Invertebrates	Fresh water
LC_{50}	2100 mg/l	24 hours	Invertebrates	Salt water
LOEC	530 mg/l	8 days	Algae and other aquatic plants	Fresh water
NOEC	430 mg/l	96 hours	Algae and other aquatic plants	Salt water
LC_{50}	5540 mg/l	96 hours	Fish (Oncorhynchus mykiss)	Fresh water
LC_{50}	11000 mg/l	96 hours	Fish	Salt water

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com

butan-1-ol				
Parameter	Value	Exposure time	Species	Environment
LC_{50}	1376 mg/l	96 hours	Fish (Pimephales promelas)	
EC_{50}	1328 mg/l	48 hours	Daphnia (Daphnia magna)	
EC_{50}	4390 mg/l	17 hours	Microorganisms (Pseudomonas putida)	
EC_{50}	225 mg/l	96 hours	Algae and other aquatic plants (Pseudokirchneriella subcapitata)	
NOEC	4.1 mg/l	21 days	Daphnia (Daphnia magna)	
EC_{50}	18 mg/l	21 days	Daphnia (Daphnia magna)	

isopropanol				
Parameter	Value	Exposure time	Species	Environment
LC_{50}	>100 mg/l	48 hours	Fish (Leuciscus idus)	
EC_{50}	>100 mg/l	48 hours	Daphnia (Daphnia magna)	
EC_{50}	>100 mg/l	72 hours	Algae (Scenedesmus subspicatus)	

Chronic toxicity

acetone				
Parameter	Value	Exposure time	Species	Environment
NOEC	2212 mg/l	24 hours	Invertebrates (Daphnia magna)	

12.2. Persistence and degradability
Data not available.

12.3. Bioaccumulative potential
Data not available.

12.4. Mobility in soil
Data not available.

12.5. Results of PBT and vPvB assessment
Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties
Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects
Data not available.

SECTION 13: Disposal considerations

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1950

14.2. UN proper shipping name

AEROSOLS

14.3. Transport hazard class(es)

2 Gases

14.4. Packing group

not relevant

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.	
UN number	1950
Classification code	5F
Safety signs	2.1



Tunnel restriction code	(D)

Air transport - ICAO/IATA

Packaging instructions passenger	203
Cargo packaging instructions	203

Marine transport - IMDG

EmS (emergency plan)	F-D, S-U
MFAG	620

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER.
P410+P412	Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox.	Acute toxicity
ADR	European agreement concerning the international carriage of dangerous goods by road
Aerosol	Aerosol
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC_{50}	Concentration of a substance when it is affected 50 % of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com

EuPCS	European Product Categorisation System
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
LC_{50}	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD_{50}	Lethal dose of a substance in which it can be expected death of 50% of the population
log Kow	Octanol-water partition coefficient
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
Press. Gas	Gases under pressure
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 7.0 replaces the SDS version from Tuesday, 27 February 2024. Changes were made in sections 2, 11, 12, 13 and 16.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.

AG TermoPasty Grzegorz Gąsowski ul. Kolejowa 33 E, 18-218 Sokoły,
tel. +48 86 274 13 42, info@termopasty.pl, www.termopasty.com