# ESC-QBLOK1202



## Specificatii

| | |
|---|---|
| Cod ETI | 003903207 |
| Descriere | ESC-QBLOK1202 |
| Denumire clasă | Bloc distribu ie |
| Tip | Blocuri terminale tip ES |
| Tensiunea nominală(V) | 500 |
| Montare | Șină tip DIN 35 mm |
| Nivel | Singura |
| Culoare | Verde |
| Sec iune transversală nominală | 10 |
| Tensiunea nominala de rezistenta Uimp (kV) | none |
| Curent maxim cu sectiunea transversala (mm2) | 63 |
| Curent maxim cu sectiunea maxima transversala (mm2) | 63 |
| Sectiunea transversala a conductorului (mm2) | 16 |
| Conexiune incrucisata | NO |
| Sectiune finala | NO |

Pagina de produse online

## Alta documentatie

Catalog caracteristici tehnice
Model 3D
Manual de instructiuni
Declaratie CE
Eplan mușchi

## ETIM clasificare internationala

| | |
|---|---|
| Clasificare | EC000897 |
| Denumire clasă | Feed-through terminal block |
| Connectable conductor cross section fine-strand without cable end sleeve | 1.5…10 |
| Connectable conductor cross section fine-strand with cable end sleeve | 1.5…10 |
| Connectable conductor cross section solid-core | 1.5…16 |
| Connectable conductor cross section multi-wired | 1.5…10 |
| Rated current In | 63 |
| Rated voltage | 500 |
| Type of electrical connection 1 | Screw connection |
| Type of electrical connection 2 | Screw connection |
| Number of levels | 1 |
| Mounting method | DIN rail (top hat rail) 35 mm |
| Material insulation body | Thermoplastic |
| Operating temperature | -40…100 |
| Inflammability class of insulation material according to with UL94 | V0 |
| Closing plate required | |
| Colour | Green |
| Internally connected stages | |