KZS-4M 3p+N A B25/0.03



Specificatii

Cod ETI	002174906
Descriere	KZS-4M 3p+N A B25/0.03
Denumire clasă	Diferen ial RCBO
Capacitatea de rupere (kA)	6
Caracteristică de întrerupere	B
Curent nominal (A)	25
Tip	A
Curent de defect nominal (A)	0.03
Tip curent	A
Tensiunea nominală(V)	415
Număr de poli	3+N
Frecven ă nominală (Hz)	50/60 Hz
Standarde	IEC/EN 61009
Sec iune transversală nominală	1-25

Pagina de produse online


Alta documentatie


Catalog caracteristici tehnice
Certificate
Model 3D
Manual de instructiuni
Declaratie CE
Eplan mușchi

ETIM clasificare internationala

Clasificare	EC000905
Denumire clasă	Earth leakage circuit breaker
Number of poles (total)	4
Number of protected poles	3
Rated voltage	400V
Rated current	25A
Rated fault current	0,03A
Leakage current type	A
Current limiting class	3
Rated short-circuit breaking capacity according to EN 61009	6kA
Frequency	50/60 Hz
Release characteristic	B
Concurrently switching neutral conductor	1
Width in number of modular spacings	4
Built-in depth	69mm
Degree of protection (IP)	IP20
Connectable conductor cross section solid-core	1…25mm²
Connectable conductor cross section multi-wired	1…25mm²

Desen cotat





Simbol/Conexiune

