ETIMAT P10 1p B20

Specificatii

Cod ETI	001901011
Descriere	ETIMAT P10 1p B20
Denumire clasă	Întrerupător de circuit
Func ie	MCB
Capacitatea de rupere (kA)	10
Caracteristică de întrerupere	B
Curent nominal (A)	20
Tensiunea nominală(V)	240
Număr de poli	1
Frecven ă nominală (Hz)	50/60
Standarde	EN/IEC 60898
Sec iune transversală nominală	1-25
Tipul voltajului	AC
Tensiunea nominala de rezistenta Uimp (kV)	6kV

Pagina de produse online

Alta documentatie

Catalog caracteristici tehnice
Model 3D
Manual de instructiuni
Declaratie CE
Eplan mușchi

ETIM clasificare internationala

Clasificare	EC000042
Denumire clasă	Miniature circuit breaker (MCB)
Release characteristic	B
Number of poles (total)	1
Number of protected poles	1
Rated current	20A
Rated voltage	240V
Rated insulation voltage Ui	500V
Rated impulse withstand voltage Uimp	6kV
Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V	10kA
Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V	10kA
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V	10kA
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V	10kA
Voltage type	AC
Type of drive	50…60Hz
Current limiting class	3
Suitable for flush-mounted installation	1
Over voltage category	3
Pollution degree	2
Additional equipment possible	1
Width in number of modular spacings	1
Built-in depth	70mm
Degree of protection (IP)	IP20
Ambient temperature during operating	-40…70°C
Connectable conductor cross section multi-wired	1…25mm²
Connectable conductor cross section solid-core	1…25mm²

Caracteristicile energiei de topire

Caracteristici

Desen cotat

Simbol/Conexiune