

## Product information

# 98 25 02 SLS

## (Slim) PlusMinus screwdriver

Pozidriv®

IEC 60900 DIN EN 60900

- Driving tips for PlusMinus profile screws
- Use with electronics installation components, e.g. automatic circuit breakers
- Reduced blade isolation diameter for recessed spring and screw elements
- Ergonomically optimised dual component handle for fatigue reduced work and optimum transmission of force
- Handle design prevents rolling
- Chrome vanadium molybdenum steel



⚡ 1000 V ⚡

### Allgemein

Article No.	98 25 02 SLS
EAN	4003773081067
point	burnished
Handles	insulating multi-component handle, VDE-tested
weight	98 g
Dimensions	212 x 123 x 35 mm
Standard	DIN EN 60900 IEC 60900

### Technische Attribute

Size	PZ/S 2
Blade length	100 mm
Handle length	118 mm
Length of non-insulated blade	18 mm
VDE tested	yes

### Classification

eCl@ss 5.1.4	21040401
ETIM 5.0	EC000144
ETIM 6.0	EC000144
proficl@ss 6.0	AAA818c006
UNSPSC 13.1	27111701

*technical change and errors excepted*

*Pozidriv® is a registered trademark of European Ind. Serv. Ltd.*

