

Non-Contact AC voltage detector

C-LOGIC 35



- Power supply: 1x12V A23S battery
- AC Voltage range: 20-1000 V
- Frequency: 50-500 Hz
- Sound and light indication
- Double molded case
- Metal detecting distance < 20 mm
- AC Voltage sensitivity adjustment
- Memory sensitivity function
- Auto power off
- Low battery indication
- Operating temperature: -10-50 °C
- Storage temperature: -20-60 °C
- Storage humidity: <85%RH
- Altitude < 2000 m
- Product size: 157mmx24mmx20mm / 6.18"x0.94"x0.78"
- Product Weight: 42g/0.09lb
- Certificate: CE/ETL/RoHS
- Safety rating: CAT II 1000V / CAT III 600 V

C-LOGIC 35

Non-Contact AC voltage detector

General	
Storage Temperature	-20°C~60°C
Humidity	<85%RH
Altitude	<2000m
Product Size	157mm×24mm×20mm/6.18"×0.94"×0.78"
Product Weight	42g/0.09lb
Certificate	CE/ETL/RoHS
Safety Rating	CAT II 1000V/CAT III 600V
Power Supply	2×12V A23S

Specs	
Non-Contact AC Voltage Detector	✓
AC Voltage Range	20~1000V
Frequency	50Hz~500Hz
Sound and light Indication	✓
Red and Green LED Light	✓
Double Molded Case	✓
Metal Detecting Distance	<20mm
AC Voltage Sensitivity adjustment	✓
Memory Sensitivity function	✓
Auto Power Off	✓
Low Battery Indication	✓
Operating Temperature	-10°C~50°C

C-LOGIC 35

Non-Contact AC voltage detector

Product Code Information	
SKU	CLOGIC35CBINT
EAN code	8435394747903
UPC code	810053670859
Pcs/export carton	100